

# PRODUCT SHEET

Plastic pull tight seal

**PL 91/38**



**Tyden Bramm**  
of Scandinavia  
Stolpegårdsvej 7  
DK - 2820 Gentofte

Type of seal	Pull tight	
Security level	indicative	
Seal body material	HDPE - polyethylene	
Seal insert material	POM - polyoxymethylen	
Tension strength	min. 180 N (approx 18 kg)	
Operating temperature	-40°C to +50°C	
Total length	380 mm	
Operating length	306 mm	
Min. diameter of application hole	4 mm	
Method of application	manual, no tools needed	
Method of removal	by hand or scissors/light cutting tool	
Technology of marking	Hot stamping, laser engraving, inkjet printing	
Marking	Text	2 lines, 8 characters, (2 x 8)
	Logo	YES
	Numbering	6, 7 digits, 1 character + 6 digits or 2+5
	Bar code	YES
Remarks to marking	Laser engraving enables higher number of digits and characters also in combination with logo. Hot stamping allows printing of text or logo only.	
Colors	white, grey, black, yellow, orange, red, blue, green	
Packing	10 pcs in bunch, 10 bunches in PE bag, 2,000 pcs in carton, carton weight 10 kg	
Use	Money and cash bags, tank valves, cabinets, lockers	

